

IDIS H.265 4K RECORDER

SUPER PERFORMANCE AND RELIABILITY



The IDIS DR-6332PS-S is a class-leading and high-performance 4K NVR that makes up part of IDIS Total 4K Solution line up, which is comprised of IP cameras, NVRs, monitors, network accessories, and recording platforms, such as the license-free IDIS Center video management software (VMS) and the enterprise-level IDIS Solution Suite.

BENEFITS

Part of a complete end-to-end solution for 4K

From capturing and recording to viewing, the IDIS DR-6332PS-S makes ultra-high definition surveillance simply possible.

Simple configuration

The DirectIP™ true plug-and-play functionality and automatic network detection/settings result in a system that is quick and easy to set up.

Cost effective

An easily installed and configured end-to-end solution, IDIS ensures low total cost of ownership through low maintenance technology, no licensing fees, and up to 50% reduction in storage space.

Stable and secure

Patented technologies make the IDIS 4K NVR robust and resilient, suitable for even the most mission critical security operations.

Future proof

The IDIS DR-6332PS-S offers the scalability and flexibility to adapt to any business or surveillance need, delivering forward compatibility with future generation technology.

FEATURES

The DR-6332PS-S features world-leading network throughput up to 350Mbps, enables exceptional image quality, including on mobile devices, leading-edge 4K video output capability, and support for H.265. The IDIS 4K NVR allows simultaneous functionality and operation, including live-view record, playback, remote access, and backup of compressed audio and video.

Four times the resolution of FHD1080p

The IDIS 4K NVR is fully optimized for the stable and high performance of all network devices, ensuring 4K live viewing and 4K recording simultaneously.

50% less storage space

Utilizing H.265, IDIS 4K NVRs enable savings of up to 50% storage space compared with H.264.

4K output support for instant playback

IDIS 4K NVRs support true 4K output, which is critical in order to both live monitor and record in 4K. When an operator needs to monitor one camera quickly, instant play back replays recently recorded video without performing search functions. The instant playback function supports direct monitoring without any other control within IDIS Center only.

Zero configuration (plug-and-play)

The DR-6332PS-S packs an array of advanced network technologies to provide true plug-and-play installation that eliminates the need for costly implementation and integration support. As with all IDIS NVRs, the IDIS 4K NVR features For Every Network (FEN), which is an automated network configuration service that simplifies installation of networked surveillance systems. FEN enables easy remote client access without the need for advanced IT knowledge.

IDIS H.265 4K Recorder

DR-6332PS-S

- Total incoming throughput 350Mbps
- Up to 960ips Full HD real-time recording
- Supports H.265 / H.264 codec
- Supports UHD display
- Up to 960ips live display
- Easy to install, set-up, and play with DirectIP cameras
- Built-in 16 channel PoE switch and expandable up to 32 Channel using DirectIP gigabit PoE switch
- Expandable up to 132TB using eSATA storage
- Supports RAID 1
- Supports one click network configuration through FEN service
- Supports third party cameras (Axis, Panasonic, ONVIF™)





SPECIFICATIONS

| VIDEO | |
|-----------------------------|--------------------------------------------------------------------------------------------------------|
| Video Inputs | 32 IP Channels |
| Max. Incoming Throughput | 350Mbps |
| Supported Camera | DirectIP, Axis, Panasonic, ONVIF |
| Video Outputs | 1 HDMI, 1 VGA |
| Display Resolution | 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200 |
| Display Speed | Up to 960ips |
| Digital Zoom | x2 ~ x12 |
| RECORDING | |
| Max. Throughput | 230Mbps, 960ips @ Full HD, 240ips @ 4K (UHD) |
| Recording Resolution | Up to 8MP (Depending on IP Camera) |
| Compression | H.264, H.265 |
| Recording Mode | Time-lapse, Event, Pre-event, Panic |
| Trigger Events | Alarm In, Audio Detection, Motion Detection, Trip Zone Tampering, Video Loss |
| PLAYBACK | |
| Performance | 16ch Full HD Synchronous Playback / 4ch 4K Playback |
| Search Mode | Time-lapse, Event Log, Thumbnail, Motion, Text-in |
| Digital Zoom | x2 ~ x12 |
| STORAGE | |
| HDD | SATA x6, eSATA x4 (Up to 6TB Capacity for Each Disk) RAID 1 Supported |
| Total Capacity | 132TB=6TB x 6 (Internal) + 4x4 (External)) |
| NETWORK | |
| Client Connection | Gigabit Ethernet (Client) x1 |
| Video In Connection | Gigabit Ethernet (IP Camera) x16 + Gigabit Ethernet (Ext) x1 |
| Transmission Speed | 50Mbps / 100Mbps (BRP Mode) |
| Camera Power | PoE (IEEE 802.3at Class 4) Supported 16 Ports, 120W |
| Remote Data Export | IDIS Player, AVI, JPG |
| Event Notification | Email [Attach Clip (.cbf) .MP4], Callback to Remote S/W Push Notification (IDIS Mobile), SNS (Twitter) |
| Two-way Audio | Yes |
| Client Viewer | IDIS Center, IDIS Mobile, IDIS Web, IDIS Solution Suite |
| INTERFACE | |
| Audio In / Out | Local (NVR): 1 RCA / 1RCA + 1HDMI IP Camera : 32 / 32 (Depending on IP Camera) |
| Alarm In / Out | Local (NVR) : 4 / 1 IP Camera : 32 / 32 (Depending on IP Camera) |
| Alarm Reset In | 1 |
| Serial Interface | RS232 (Terminal Block), RS485 (Terminal Block) |
| USB | USB 2.0 x 1, USB 3.0 x 1 |
| User Interface | Mouse, IR Remote Control, Network Remote Keyboard |
| GENERAL | |
| Operating System | Embedded Linux |
| Unit Dimensions (W x H x D) | 430mm x 88mm x 410.8mm (16.9" x 3.5" x 16.2") |
| Unit Weight | 6.0kg (13.2lb) (with 1 HDD) |
| Working Temperature | 0°C to 40°C (32°F ~ 104°F) |
| Operating Humidity | 0% ~ 90% |
| Power Input | AC 100-240 V, 50/60Hz, 3.0 - 1.5A |
| Power Consumption | Max. 200W (with 6 HDDs) |
| Approvals | FCC, UL, CE, CB, KC |

DIMENSIONS



(Unit - mm)



- 1 Factory Reset Button
- 2 Video In / PoE Ports
- 3 Video In / Ext. Port
- 4 Network Port
- 5 eSATA Ports
- 6 Alarm Connection Ports
- 7 RS-485 Port
- 8 RS-232 Port
- 9 HDMI Out Port
- 10 VGA Out Port
- 11 Audio Ports
- 12 Power In Port
- 13 Vent

ACCESSORIES (OPTIONAL)



DH-2212PF



DA-ES1104

IDIS HQ

IDIS Tower, 344 Pangyo-ro
Bundang-gu, Seongnam-si
Gyeonggi-do
Republic of Korea, 463-400

T +82 (0)31 723 5400
F +82 (0)31 723 5100
E sales@idisglobal.com

IDIS America

801 Hammond Street
Suite 200
Coppell, TX 75019
U.S.A.

T +1 469 444 6538
F +1 469 464 4449
E sales_americas@idisglobal.com

IDIS Europe

1000 Great West Road
Brentford, Middlesex
TW8 9HH
The United Kingdom

T +44 (0)203 657 5678
F +44 (0)203 697 9360
E uksales@idisglobal.com

IDIS Benelux

De Slof 9
5107 RH
Dongen
The Netherlands

T +31 (0)162 387247
F +31 (0)162 311915
E sales@bnl.idisglobal.com

IDIS Middle East

P.O. Box 341037
D-308, DSO HQ Bldg
Dubai Silicon Oasis
Dubai, UAE

T +971 4 501 5434
F +971 4 501 5436
E sales_mena@idisglobal.com