



SITERWELL
Smart Security Ecosystem



SiterOne

ALL IN ONE

SiterOne Secure You Home Wisely



SECURITY ALARM

- Motion sensor
- Shock sensor
- Touch keypad
- Multi-sound alarm siren
- Photo and video messages
- 24/7 central monitoring
- Remote control with smartphone



HOME AUTOMATION

- Remote control with smartphone
- Online rule creator
- Scene manager
- Room manager
- Z-Wave, Philips Hue, Bluetooth...



ELDERLY CARE

- Motion sensor
- Automatic check calls
- Sound reminders



WALL PANEL

- Room temperature
- Room illuminance
- Room humidity
- Weather forecast
- Scene controller



THERMOSTAT

- Gas/floor heating
- Temperature meter
- Exterior temperature meter
- Air condition control
- Remote control with smartphone



INTERCOM

- Door phone control
- Remote control with smartphone



IP CAMERA

- Live video stream
- Remote control with smartphone
- Built-in CAM
- External CAM as option

COMPATIBLE WITH



SiterOne

SiterOne is a 8-inch security and home automation panel powered with Android operating system and running with intelligent home security and automation software. It supports and controls Z-Wave Plus devices including: power plug, PIR (motion sensor), CO detector, smoke detector, door contact and many. The 8-inch super clear capacitive touchscreen and intuitive user interface greatly helps installation and operation.



TECHNICAL SPECIFICATION

- ↻ **APPLICATIONS**
 Security System
 Thermostat
 Elderly Care System
 Home Automation
 Video Monitoring
 Intercom
 Room Controller
- ↻ **SYSTEM**
 ARM Cortex-A7, Quad-core 1.3GHz CPU
 1024MB RAM
 Android 5.1 Lollipop
- ↻ **NETWORK**
 Wi-Fi 802.11 b/g/n
 Bluetooth
 Philips Hue
 Z-Wave+ (500 series)
 3G(900/1900/2100)
 LTE
- ↻ **SENSORS SUPPORT**
 Noise
 Light
 Humidity
 Temperature
 Motion
 Remote Controller
- ↻ **POWER**
 Power input: 5VDC
 Power supply input: 100-240VAC, 50/60Hz
 Backup battery: 4300mAh
- ↻ **INPUT/OUTPUT**
 Touch sensitive 8" screen, 800x1280 px
- ↻ **ACCESSORIES**
 Wall socket adapter
 Wall holder
 Screws
 Table stand
- ↻ **PHYSICAL DIMENSION**
 219(W) x 126(H) x 9.4(D) millimeters
- ↻ **WEIGHT**
 369g
- ↻ **ENVIRONMENTAL**
 Operating temperature: -10°C to 55°C
 Storage temperature: -30°C to 70°C
 Humidity: less than 98% non-condensing
- ↻ **REGULATION**
 Safety: UL power supply
 EMC: FCC, CE
 RoHS
- ↻ **WARRANTY**
 1 year standard