

KONGTOP

Professional R&D Manufacturer

www.kongtop.cn



Specifications (D1 SERIES DVR)

Model	KT8808FD		KT8816FD	
Operating system	Embedding Linux OS			
Video Compression	Main Profile H.264			
Video Input	8CH BNC		16CH BNC	
Video output	1CH BNC,1CH SPOT,1CH VGA(1280*1024),1CH HDMI(1920*1080P)			
Audio Input/Output	8CH RCA/1CH RCA		16CH RCA/1CH RCA	
Display Picture	1/4/8CH/PIP/ZOOM		1/4/9/16CH/PIP/ZOOM	
Multiplex Operation	Live/Display/Playback/Recording/Backup			
	Mobile phone Surveillance/Network simultaneously			
Display Resolution	PAL:D1(704*576),NTSC:D1(704*480)			
Recording Mode	Manual/Timer/Motion Detection/Remote			
Recording Frame Rate	PAL:D1@200fps NTSC:D1@240fps		PAL:D1@400fps NTSC:D1@480fps	
Recording Resolution	PAL:D1(704*576),HD1(704*288),CIF(352*288)			
	NTSC:D1(704*480),HD1(704*240),CIF(352*240)			
Recording Playback	1/4/8CH playback		1/4/16CH playback	
Recording Backup	USB, Moved Hard Disk, USB Writer, Network			
Network transmission	D1, HD1, CIF Recording and playback.			
Recording Play	Special player, support AVI File Format Conversion			
Alarm In/Out	8CH/4CH		16CH/4CH	
Email Alarm	Send pictures to the designated email			
Alarm-action	Support			
PTZ protocol	PELCO-D, PELCO-P			
PTZ	Support PTZ preset, Cruise and Control PC via PC			
HDD	4 SATA HDD or 3 SATA HDD+ 1 ESATA OR 2 SATA HDD+1 BUILT-IN DVD WRITER +1 ESATA			
HDD capacity	2TB each HDD(Max storage: 2TB*4=8TB)			
Network port and Protocol	RJ-45 10/100M via Ethernet, Support TCP/IP, PPPOE, DHCP, DDNS, UPNP			
Browser	Windows XP/Vista/Win 7/Mac OS, IE6.0-9.0/Firefox/Chrome/Opera/Apple Safari			
Client software/CMS	Support(One CMS for at most 100 DVRs), free supply to use			
Mutil-language	Support			
SDK Package	Available			
Mobile Phone Surveillance	Support Android, iPhone, Blackberry, Symbian, Windows CE OS			
Dual-stream	Support(Main and secondary interchange)			
Mouse interface	USB1.1			
Backup interface	USB2.0			
Remote Controller	Support			
Power	DC 12V/6A			
Working Temperature	0~50℃			
Working Humidity	10%~90%			
Size(mm)	430(W)x345(D)x66(H)	360(W)*250(D)*66(H)	430(W)x345(D)x66(H)	360(W)*250(D)*66(H)

