



## CERTIFIED safes for key storage

Attested at the Norwegian Building Research Institute by awarding a **FG** certificate of the Insurers Union Certified according to the burglary resistance standard PN-EN 14450: 2005 (U) for **S1** class.

**SC**  
key storage

- The housing and the doors are welded from 4 mm thick steel.
- Protection layers from reinforced and non-reinforced steel throughout the whole height of the locking mechanism.
- Stiffening edges on the internal side of the ceilings
- The safe door is locked with latches of  $\varnothing$  18 mm in diameter moving in 3 directions
- The mechanism is easily controlled with a hand wheel.
- When trying to knock off the lock, the mechanism is blocked.
- On the hinge side the door is immobilized with a special immovable plate throughout its whole height.
- The front frame is formed so that the "box" type door edges slipped into the inside thus forming an especially firm coupling.
- 8-plate safe lock is installed in the safes.
- The lock model may be altered or an additional electronic code lock may be installed at the client's request.



Model	Dimensions	Weight Kg	Capacity (l)	Complete set
	Height*Width*Depth (mm)			
SC49/14,5	490*360*145	40	35,3	96 keys inside
SC60/11,5	600*540*115	55	33,7	96 keys on the door+ 80 keys inside
SC60/20	600*540*200	70	60,5	96 keys on the door+ 400 keys inside

**SC60/20**

The distance between hooks is 29.14 mm, what allows hanging a bundle of 3-5 keys.

Model	Dimensions	Weight Kg	Capacity (l)	Complete set
	Height*Width*Depth (mm)			
SC49ro57	490*360*145	40	35,3	36 keys inside + 21 key on the door
SC60ro112	600*540*200	70	60,5	96 keys on the door+ 400 keys inside



**SC160-1296**

The distance between hooks is 40.0 mm, what allows hanging a bundle of 5-8 keys.

Model	Dimensions	Weight Kg	Number of spaces	Complete set
	Height*Width*Depth (mm)			
SG160-1296	1600*600*450	210	1296	288 spaces on the door + 6 movable panels with 1008 hooks
SG160-1872	1600*600*450	230	1872	288 spaces on the door + 6 movable panels with 1584 hooks
SC160-1968	1600*600*700	280	1968	288 spaces on the door + 6 movable panels with 1680 hooks
SC160-2928	1600*600*700	301	2928	288 spaces on the door + 6 movable panels with 2640 hooks
SC190-5616	1900*850*700	550	5616	816 spaces on the door + 6 movable panels with 4800 hooks

The distance between hooks is 29.14 mm, what allows hanging a bundle of 3-5 keys.