



Key Features:

- EI120 Fire Rating
- Can be retrofitted
- Low profile
- Highly flexible for easy installation
- Only one layer required

TENMAT's Vent Duct OverSleeve offers 120 Minutes Fire Rating to Semi Rigid Ducting. The low profile (4mm thick) OverSleeve is supplied flat and simply wrapped around the ducting and resealed with the reinforced foil backing layer. It's design allows the product to be retrofitted.

TENMAT's Vent Duct OverSleeve has been independently tested in accordance with EN1366-3 and achieves a fire resistance classification of EI120 (according to EN13501). This means that the product is able to prevent the spread of fire for 120 minutes. It was tested in partition walls without additional metal sleeving.

Product Dimensions

Duct Size	Thickness	Width	Length
75 mm	4 mm	260 mm	250 mm

Fitting Instructions

- Simply wrap sleeve flush around the duct, peel back backing tape, and press adhesive to the wrap to seal
- Cut 86 mm diameter hole in partition, & slide duct with OverSleeve into partition
- Seal edges with intumescent sealant
- Ensure OverSleeve protrudes minimum 50 mm on both sides of partition

Test Data

Report Type	Fire Test Lab	Report Number	Construction	Fire Rating
Fire Test	Chiltern Fire	RF13219	Plasterboard	120