Premier Elite SmartKey Texecom





Interact, control and monitor your security system with the Premier Elite SmartKey. Simple and intuitive to use, this intelligent wireless keyfob allows users to arm, part arm and disarm their system from anywhere in the vicinity of their property.

The Premier Elite SmartKey now features a replaceable battery and an integral RFID proximity tag. The RFID proximity tag is ideal for use with compatible keypads, freeing up the wireless keyfob to control outbuildings or to act as a dedicated panic alarm.



- · Remote arm, part arm and disarm
- · Integral RFID proximity tag for use with compatible proximity readers
- Alarm system status display
- Programmable two button panic alarm
- Remote control of up to 3 programmable outputs. Typical applications include garage door control, external lighting control and automatic gate control
- Replaceable lithium CR2 battery offers 2 to 3 year typical battery life
- PD6662: 2010, EN50131-1, EN50131-3, EN50131-5-3 Grade 2 Class II





www.texe.com Sales: +44 (0)1706 220460

Premier Elite SmartKey **Texecom**





The Premier Elite SmartKey connects to wireless systems that feature *Ricochet* Mesh Technology. Ricochet enabled wireless devices receive and repeat messages from other devices. The size, scalability and range of the entire system are extended as wireless signalling is no longer limited by point-to-point communications.

Outstanding features



Remote arm, part arm and disarm

The Premier Elite SmartKey features dedicated buttons for arm, part arm and disarm, giving instant access to these user features.

Programmable two-button panic alarm

Press the 'disarm' and 'power' buttons down for 4 seconds will activate a panic alarm. This feature is installer programmable and can be disabled if

Alarm system status display

Dedicated arm, part arm and disarm status LEDs provide users guidance on alarm status before entering the property.

Replacable lithium CR2 battery

The Premier Elite SmartKey now features a user replaceable battery. Simply pop open the rear cover with a flat terminal screwdriver to access the battery compartment.

Typical applications and user functions	
Arm, part arm or disarm an alarm system	
Trigger external lights when approaching or leaving the property	
Open or close powered gates and garage doors	
Control outbuildings – garages, sheds, external buildings	
Obtain alarm system status before entering the property	
RFID proximity tag for use with compatible keypads	
Each Premier Elite SmartKey can be assigned to a unique system user	
Superior wireless technology extends range and improves performance	

Standards & Specifications	
Alarm Systems:	EN50131-1, EN50131-3, PD6662,
	EN50131-5-3 Grade 2 Class II
EMC:	EN50130-4: 2011
	ETSI EN301 489-03 V1.4.1
R&TTE:	ETSI EN300-220 (V2.1.1)
Environmental:	EN50130-5: 2011
Frequency Band:	868.0 - 868.6 MHz
Dimensions	88mm x 21mm
Weight	30g approx

