

400-650-1780

www.guard361.com

# LANDUELL®

### Beijing Landwell Electron Technology Co., Ltd

### **Cloud Guard Tour System G-100**

**Configuration Sheet** 

Latest Update: January, 2019





# LANDWELL

#### About G-100

G100 proximity guard tour patrol applies for **RFID** technology, professionally designed for guard patrolling. It effectively supervises, manages and assesses the working conditions of patrol personnel and strengthen safety management. The system can be widely used in community, property patrols; railway, oil pipeline, power and public security inspections.

#### System Description

<u>Hardware</u>

- Windows, NET 4.0
- USB Interface and CD-ROM drive Available
- Resolution: Minimum 1366\*768 Maximum: 1020\*1080 display

| Material          | Plastic + Rubber                        |      |
|-------------------|---|------|
| Alert             | Vibration and luminescence (LCD)        |      |
| Record Allowed    | 40000                                   |      |
| Communication     | Magnetic / drive-free USB2.0 full speed | GIOD |
| Battery           | 1800mAH                                 |      |
| Charging Time     | 2-3 hrs                                 |      |
| Stand-by          | > 1 month                               |      |
| Low Battery Alarm | Power reminder                          |      |
| Protection Grade  | IP68                                    |      |
| Size              | 48.7mm*26.5mm*150mm                     |      |
| Weight            | 222g±4g                                 |      |
| Brightness        | 400lm                                   |      |

## Accessories

#### **Location Button**

| Item No.: ID-EM-10                                |  |
|---|--|
| Size: 70mm*32mm * 8mm                             |  |
| Temperature: -25℃~65℃                             |  |
| Material: Engineering plastic polycarbonate       |  |
| Frequency: 125KHZ                                 |  |
| The round holes on both sides can be fixed on the |  |
| object with 6mm screws, and the internal is       |  |
| encapsulated with epoxy engineering resin, which  |  |
| is time-resistant and anti-corrosion and suitable |  |
| for poor environment.                             |  |



# LANDWELL

#### **Personnel Button**

| Item No.: ID-EM-P2                            |            |
|---|------------|
| Frequency: 125KHZ                             |            |
| Temperature: -25℃~65℃                         | - All      |
| Size: 50mm*35mm                               |            |
| Technical indicators: according to the        | (antimate) |
| specific name of the patrol personnel, assign |            |
| the corresponding name to the personnel       |            |
| button.                                       |            |

#### **Magnetic Charging Cable**

| Delay: 5.02NS/m                           |  |
|---|--|
| Impedance: 107-110hm                      |  |
| Length: 1M                                |  |
| Description: Magnetic drive-free charging |  |



Sherry Yu Technical Support | Sales Consultant T: +86 10 8471 7640 M: +86 150 9762 7971 E: sherry@land-well.net www.land-well.com www.guard361.com

