

2MP 62X Outdoor Heavy Duty AR PTZ IP Camera



Model NO.	ARC0262C
Monitor Distance	
IR Distance	2500-3000m
Day Vision	6000-8000m
Camera	
Effective Pixels	1920×1080
Image Sensor	1/1.8" Progressive Scan Cmos
Minimum Illumination	Color: 0.003 Lux; B/W: 0.0017 Lux
Image Settings	Saturation/brightness/contrast /sharpness
White Balance	Support
WDR	Support
HLC	Support
BLC	Support
DNR	Support
Defog	Support
Auto diaphragm	DC drive
Exposure Mode	Auto/Manual
Shutter	1/1~1/100000s
Video Format	Main code stream (1080P, 720P) Auxiliary code flow (D1, CIF)
Video Bit Rate	32 Kbps~8Mbps
Frame Rate	50Hz: 50fps 60Hz: 60fps
Video compression	H.264、H.265
Overlaying information of OSD	Support to add OSD overlay information autonomously.
Day& Night	Support IR-CUT double filter switching
Lens	
Image Plane	1/2"
Focal Length	12.5mm~775mm
Optical Zoom	62X
Aperture Range	F3.5~CLOSE
Horizontal Field of View	0.5°~26°(±30%)
Defog	Support
Parfocality	Support
AR Technology	Accurate correction and discrete correction in real time, adaptive dust-fog control technology (adjust the contrast of gray-white image in dust-fog environment and restore the original color)suitable for low-exposure and dust-fog monitoring.
Laser Lens	The zoom, focus, laser illumination spot size and light intensity of the imaging lens can achieve the linkage. When the lens of the camera system is doubled, the laser spot Angle can automatically follow the linkage to keep both in the best state all the
Laser	
Laser Power	17W
Laser Wavelength	810nm±5%
Illuminating Angle	0.5 ° ~ 22 °supports remote electric control.
Fiber Length	0.5m with built-in laser protection power.

Laser	Military grade lasers can be used continuously and have a long life.
Fiber Bundle	The fiber energy output is concentrated and no scattering.
High Power Single Beam Laser	Due to the poor coincidence of the spots of multi-beam laser, and the difficulty of collimation adjustment and laser shaping of multi-beam laser, the single-beam laser effectively increases the image effect and system stability.
Pan & Tilt	
Typical Load	50KG
Pan rotation Angle	360°
Tilt rotation Angle	-35° (up) ~50° (down)
Pan rotation Speed	0.05~10°/s
Tilt rotation Speed	0.05~6°/s
Number of Preset	255
Precise Positioning	≤0.1°
Protection Level:	IP66
Pan & Tilt Control	Pan & Tilt direction, focus, zoom, aperture and other functions of control.
Auto Scan	Support
Patrol	Support
Trace Scan	Support
3D Positioning	Support
Interface	
Video Analog Output	1Vp-p Composite Output (75Ω/BNC)
Network Port	1CH 10/100BaseT Ethernet , RJ45 Port
Network Protocol	IPv4,HTTP,DNS,NTP,RTSP,RTP,TCP,UDP
Control Interface	1RS-485 interface, supportPELCO-D Protocol
Alarm Input/Output	Support
AR Technology	
Adding Tags	Support add 250pcs tags information for any target objects in the ARC surveillance screen.
Multi-layer Display	All tags can be displayed in multi-layer way in ARC surveillance screen, it shows different multilevel tags with zoom in and zoom out.
Tag Search	ARC can search and position the target object in monitoring range according to tag search to quickly move the PTZ to corresponding tags position and intelligent zoom in and zoom out for best surveillance viewing.
Video Linkage	Support picture in picture multi-display video from various CCTV CAMS and mobile devices and direct operate PTZ camera.
Video Storage	Support video storage with tag information
Video Playback	Support video playback with tag information
Posture Perception	Perceive the current lens orientation (heading Angle, pitch Angle, field of view Angle) and record.
Data Association	video is associated with the coordinates, time, and orientation of the camera at that time.
Information Integration	
Alarm Linkage	Preset/Patrol/Trace
Heartbeat Mechanism	Support
General Function	Anti-scintillation, double code flow, password protection, watermarking technology.
Intelligent Alarm	Motion detection/IP address conflict
General	
Sun Shade	All aluminum alloy materials, with the use of outdoor protective hood.
Hood attachment	All stainless steel aviation plug
Wiper	For optional
Salt-spray proof	Spray continuously for 48 hours at a PH of 6.5 ~ 7.2
Working Temperature	-40°C~+60°C
Power Supply	AC24V
Dimensions	725mm×391mm×608mm
Weight (approx.)	48KG
Power Consumption	≤220W