

# SINGLE/DUAL-PATH COMMUNICATOR FOR THE ALARM BUSINESS



## MX03-LTE-M



### **FUTURE-PROOF LTE-M TECHNOLOGY**

with Dual-SIM, each supporting multiple operators per country



### **FAST AND EASY INSTALLATION**

with any panel using Contact ID, SIA, Pulse and FF 4/2



### **RELIABLE DATA REPORTING**

to any Alarm Receiving Center



### **IMPROVED RECURRING REVENUE**

Low flat-rate monthly fees for improved profitability

## MAIN FEATURES

**REPORTING FORMATS** – Dial Capture Interface supporting Contact ID, SIA, Pulse and FF 4/2

**EXCEPTIONAL REDUNDANCY** – Dual-Path, Dual-SIM device, each SIM supporting multiple operators

**SUPERVISED CONNECTIVITY** – 10-minute polling of the connection

**ADMIN PORTAL** – Online-based device management portal and monitoring of user accounts

**FULL EVENT REPORTING** – Reliable reporting to any Alarm Receiving Center

**INSTALLER MOBILE APP** – Real-time on-site communication diagnostics and device configuration

**UNIVERSAL PANEL COMPATIBILITY** – Works on 12 to 29 VDC, supporting a wide range of alarm panels

### SPECIFICATIONS

- Multi-band CAT-M1 LTE  
700/850/1700/1900/2100 MHz
- Dial Capture interface supporting CID, SIA, Pulse and FF 4/2
- Up to 6 inputs, 2 digital & 1 relay outputs
- Supply voltage: +12 to +29 VDC
- Consumption: Standby 50mA, Peak 200mA
- Dimensions: 63 x 90 x 32 mm
- Weight: 100g without antenna

### CERTIFICATIONS

- EN 50131
- EN 50136

### RCONTROL ADMIN MOBILE APP

